


MS-SB17-H

Lens Technology Enabled™ Base-Station Antenna perfect for stadium applications, utilizes a patented spherical lens design with 1 isolated high-frequency (1710-2690MHz) cross-polarized beam. Beam has 2 cross-polarized ports for supporting 2X2 MIMO and low side-lobes.




PATTERN RESULTS:

High-Band Horizontal Pattern (1.80GHz)



High-Band Vertical pattern (1.80GHz)



TECHNICAL SPECIFICATIONS	
Frequency	1710-2690 MHz
Gain	19.5dBi
VSWR	<1.5:1
Polarization	Dual Slant ±45
Horizontal Coverage	40°
Horizontal Beamwidth (10dB)	30°
Vertical Beamwidth (10dB)	30°
Total Number of Beams	1
Number of Ports per Beam	2
First Sidelobe Level	<-20dB
Front to Back Ratio	>28dB
Isolation Port to Port -Polarization	>28dB
Power Rating	250W per port
Intermodulation	<-153dBc
Impedance	50 ohm
Connector Quantity and Type	2 x 4.3-10 female

MECHANICAL DATA	
Dimensions (H x W x D)	44 x 44 x 62 cm
	17 x 17 x 24.5 inch
Antenna Weight	7 kg
	15.4 lbs
Radome Material	Polycarbonate
Mounting	TBD
ENVIRONMENTAL RATINGS	
Humidity	95% RH @ +30°C
Temperature	-40°C to +70°C
Wind load (Lateral)	TBD

Connector Layout

